

# Trap Modules



UKL Trap Modules are available in two versions:

**The open loop:** Where the condensate is let out to the atmosphere, and consists mainly of one inlet Isolation, Bypass valves and a Steam Trap.

**The Closed loop:** Where the condensate connected for recovery, consist with Valves upstream and downstream isolation and Bypass, Strainer (for Ball Float), Steam Traps, Sight Glass, Non-return valve, Sight Glass, diffusers (for TD trap) etc.

Available in Carbon Steel, Stainless steel construction.

- 15mm to 25mm Complete Fabricated Modules with Thermodynamic & Thermostatic steam traps
- 15mm to 50mm Complete Fabricated Modules with Ball Float type steam traps

It is cumbersome, occupies more space and involves a number of joints, piping components, Welding and other process and statutory certification in most cases and is extremely time consuming.

Pressure rating ASA#150 and #300. In open [T type] as well as Closed [D type] configurations.

In view of technical progress designs and dimensions are subject to change without notice.



**UNI KLINGER LIMITED**

*A joint venture of the Neterwala group of companies and KLINGER AG, Switzerland.*



**HARSH ENGINEERING SALES & SERVICE PVT. LTD**

**Only Authorized Dealers for UNI KLINGER products, Telangana**

Add: 2-3-692/22/13 Lal Bagh, Zinda Tilismath Road, Ganga Nagar, Amberpet, Hyderabad - 500013  
Tel: +91-40-2740 3329 | Website: [harsh-engineering.com](http://harsh-engineering.com) | E-mail: [sales@harsh-engineering.com](mailto:sales@harsh-engineering.com)